Adhesives for interior and exterior

Cemen Power

JAIA F/★★★★4VOC Standard confirmed

Features	 Contains aggregate, so strong adhesive strength can be obtained by simply mixing with cement. Environmentally friendly adhesive. (Conforms to JAIA F***/4VOC standards) It can be applied even when the substrate is wet. Large tiles can also be applied.
Applicable tiles	Various ceramic tiles, large tiles, ceramic plates, bricks, marble, and other stone materials (Requires our "A Primer" treatment)
Applicable Place	Bathroom, toilet, kitchen, washroom, entrance, exterior wall, floor, etc.
Applicable substrate	Mortar, plywood (underlayment), ALC board Mortar, plywood (underlayment), ALC board ("A Primer" treatment), Silica board ("A Primer" treatment), FRP board ("A Primer" treatment) * Cannot be used for FRP waterproofing.
How to use	 Remove dust, oil, and dirt from the substrate. mix 1-part Cemen Power with 0.8 to 1 part cement. Use up the cement mixture within one hour. When attaching the tiles, thoroughly crimp the tiles one by one. Apply immediately after application and within 20 minutes (at 23°C). For plywood base, make a loose mortar of Cemen Power vs. Cement [1:0.8], make a crevice of about 5 mm, rub it on the plywood, dry it, and then apply mortar of [1:1] to the tiles. Fill the joints at least one day after application. **For natural stone, we recommend applying our "A Primer" to the back of the stone beforehand. **Recommended usage : 3~5 kg/m² (when mixed with cement) Cemen Power 20kg + 20kg cement can be used for 8-13 m².

Precautions for use	 Avoid direct sunlight and be careful of temperature changes. (0°C or higher) Do not store in direct sunlight. Use our "BANNO" for commercial bathrooms. The data is based on laboratory data, so conditions may differ from those of on-site installation, and the catalog values may not be satisfied. Please refer to the Safety Data Sheet (SDS) if you need more detailed information.
LINEUP	○20kg cans ○5kg cans